

MICROMETER Pneumatic & Manual

Code. N1102 and N1102P

To measure the thickness of board.

Applicable Standard: ISO 534, ISO 12625-3, TAPPI T411



Foot switch for
pneumatic model

MODELS:

N 1102 - Manual model: 10 cm² measuring pin

N 1102P - Pneumatic model: 10 cm² measuring pin

CONNECTIONS:

Electricity: battery

Compressed air: approx. 400 kPa (only on the pneumatic model)

WEIGHT AND DIMENSIONS (EQUIPMENT ONLY):

200 x 250 x 300 mm (WxDxH) / 12 Kg

WEIGHT AND DIMENSIONS WITH PACKAGING:

400 x 400 x 400 mm (WxDxH) / 16 Kg

Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169



PAPER TESTING ASSOCIATION

CORRUGATED BOARD Testing Equipment

DEVICE DESCRIPTION:

The robust micrometer is available in either pneumatic or manual configuration. Depending on the model, the device is operated via a hand lever or a pneumatic foot pedal. The descending speed acc. to standard is set with a throttle. A battery powered digital measurement gauge is mounted on the device for displaying the measurement results.

TEST DESCRIPTION:

Depending on configuration, the measuring pin is lifted via the pneumatic foot pedal or manually with the lever mounted on the side, and the sample is placed in the measurement area. Then the pedal or lever is released, and the measuring pin lowers at a speed limited by the throttle onto the sample. The digital measurement gauge displays the result of the measurement.

SPECIFICATIONS:

- Bound the lowering speed via a throttle
- Battery operated digital measurement gauge
- Resolution: 1 μm , reproducibility: $\pm 2 \mu\text{m}$
- Model with manual control.
- Measuring range 0 - 25 mm
- Measuring accuracy 0.01 mm
- Measuring surface 10 cm^2
- Measurement pressure 20 kPa

Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169