

Large-Size Centrifugal Dehydrator (Suspended type with three legs)

Model No. 2537

This machine rapidly dehydrates pulp slurry. Unique suspended design completely offsets unbalance in rotation. Low noise of rotation. The brake immediately stops the operation.

	<i>Inner diameter</i>	<i>Depth</i>	<i>Capacity</i>	<i>Rotation Speed</i>	<i>Motor</i>
A	240mm	140mm	3 liters	3000rpm	0.4kW
B	300mm	160mm	4.5 liters	3000rpm	0.75kW
C	405mm	200mm	12 liters	2000rpm	1.5kW
D	455mm	210mm	15 liters	1800rpm	1.5kW



Specifications

Material of Section in

Contact with Liquid: SUS-304 (stainless Steel)

Optional: filter cloth, rotation control with inverter

Power Source: A, B 100/110VAC 50/60Hz 9A
C, D three-phase 200/220VAC 50/60 Hz 7A

Outer Dimensions: A 550 x 710 x 570mm Instrument weight 78kg
B 620 x 850 x 610mm Instrument weight 100kg
C 830 x 1100 x 610mm Instrument weight 250kg
D 830 x 1100 x 610mm Instrument weight 270kg

Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169