

DISINTEGRATOR with Acrylic Pot

Code. N62XX

For disintegration of pulp suspensions acc. to different standards. Lightweight pot made from acrylic glass or heavy stainless-steel pot

Standards: ISO 5263-1 / SCAN C18 M2 / TAPPI T205 / PAPTAC C.6

SPECIFICATION

- Made from robust stainless steel and aluminum
- Hinged head for easy take-out of the vessel
- Safety interlock
- Motor: 370 W
- Digital display of the revolutions
- Agitator speed according to standard: 2,980 +- 30 rpm applicable for TAPPI and ISO

DELIVERY CONTENT

- Disintegrator
- Acryl pot
- Measuring gauge
- Calibration certificate
- Operation manual
- Connection cable

MODELS:

- N6210 - Disintegrator with acrylic pot
- N6220 - Disintegrator with stainless steel pot

CONNECTIONS:

Electric: 230 V / 50 Hz

WEIGHT AND DIMENSIONS (ONLY MACHINE):

270 x 400 x 460 mm (WxLxH) / 36 Kg

WEIGHT AND DIMENSIONS WITH PACKING BOX:

350 x 500 x 600 mm (WxLxH) / 56 Kg



Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169