



SOMERVILLE shive content analyzer

Code.N7100-A

For determination of shives and other particles in pulp suspensions

Standards: TAPPI T275 / TAPPI UM242 / PAPTAC C.11P



Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169



PULP Testing Equipment

SPECIFICATION

- Control box prepared for wall fastening
- Calibrated ring nozzle (works with 8.6 l/min at a pressure of 123.6 kPa)
- Sturdy construction made of corrosion-resistant materials only
- All parts in contact with water are made of non-corrosive material
- Somerville unit is mounted on a stand and a control box is prepared for wall fastening
- Drive motor protection class IP55 built into the stand, drives the slot screen via an excentric mechanism at approx. 690 700 U/min
- Control (start/stop/water), timer for 20 min sieving time (motor and water) and thermal overload protection built in electric control unit (IP65)
- Air pistol delivered complete with tube and self-sealing coupling for cleaning the slot plate and water box
- Will be delivered ready for use

DELIVERY CONTENT

- Shive content analyzer with control box for wall fastening
- · Air pistol for cleaning
- Calibration certificate
- Operation manual
- Connection cable

OPTION:

- Slote plate with 5 mm
- Slote plate with 0,08 mm
- Slote plate with 0,10 mm
- Slote plate with 0,12 mm
- Slote plate with 0.13 mm
- Slote plate with 0,15 mm
- Slote plate with 0,20 mm
- Slote plate with 0,25 mm

Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169





CONNECTIONS:

Electric: 230 V / 50 or 60 Hz

Water: Drinking water quality min. 1 bar (200 kPa),

Drainage 50 mm diameter

WEIGHT AND DIMENSIONS (ONLY MACHINE):

700 x 620 x 1200 mm (WxLxH) / 100 Kg

WEIGHT AND DIMENSIONS WITH PACKING BOX:

 $800 \times 750 \times 1300 \text{ mm} (WxLxH) / 130 \text{ Kg}$

Sold & serviced by:

OpTest Equipment Inc.

www.optest.com - sales@optest.com - +1-613-632-5169